

FIRE SAFE STAINLESS STEEL THROTTLING GLOBE VALVES

Outside Screw & Yoke – OS&Y
LIQUEFIED NATURAL GAS
CLASS 150
Bolted Bonnet – Extended
DN100 – DN300 (4 " – 12 ")

Bestobell Valves have been manufacturing cryogenic valves for over forty years. We have a reputation for product innovation, product reliability and engineering excellence.

Description

Class 150 stainless steel extended globe valve with bolted bonnet and integral metal seat. Available with butt weld and flanged end connections, the valve has a conical seat design for tight shut off. The bolted bonnet allows for simple site maintenance, with easy access to the serviceable parts of the valve.

ISO 9001 accreditation
General design in accordance with BS6364
Flanged end connections to ANSI B16.5
Butt Weld end connections to ANSI B16.25
Shell minimum wall thickness in accordance with B16.34
Optional full material traceability backed by BSEN 10204 3.1 / 3.2 Certification

Features and Benefits

- Designed and manufactured for use with LNG, LPG and other flammable gas service
- Temperature range -196°C to +80°C
- 316 Stainless Steel construction for marine applications
- Fire safe approved to BS EN ISO 10497:2004
- Loose bolted bonnet design allows for thermal expansion and contraction and eliminates leakage at the bonnet gasket
- Anti-blow out stem for operator safety
- Actuator supplied to customer's specifications designed for marine applications
- Bolted bonnet allows for simple site maintenance, with easy access
- Disc profile engineered to enhance throttling flow characteristics
- The disc is securely fixed to a non-rotating rising stem, reducing operational noise




FIRE SAFE STAINLESS STEEL THROTTLING GLOBE VALVES

Outside Screw & Yoke – OS&Y
LIQUEFIED NATURAL GAS

CLASS 150

Bolted Bonnet – Extended
DN100 – DN300 (4" – 12")



Materials

Body	SS ASTM A351 CF3M/CF3M
Bonnet Weld Assy.	SS ASTM A351 CF3M SS ASTM A312/316L BS EN 10088-3 1.4404 (316L SS)
Loose Bonnet Flange	SS ASTM A351 CF8M
Stem	BS EN 10088-3 1.4401 (316 SS)
Disc	BS EN 10088-3 1.4401 (316 SS)
Gland Packing	Carbon / Graphite
Gasket	SS Reinforced Graphite
Fasteners	SS Gr. A4-80 BS6105 Type 316

Construction

Bolted bonnet / loose flange
Extended stem for cryogenic service
Flanged or butt weld ends
Metal to metal seats
Actuator c/w manual override

Specifications

Class 150

	'A'	Ø 'B'	Ø 'C'	'D'	'E'	'F'	'G'	'H'	Ø 'I'	'J'	'K'	'L'	Weight (Kg)
DN100 RF	<i>Please contact Bestobell LNG for specifications</i>												
DN200 RF	495	203	343	29	650	1284	473	200	365	8	22	298	253
DN200 BW	495	203	238	N/A	650	1284	473	200	365	N/A	N/A	N/A	224
DN300 BW	698	305	333	N/A	750	1391.5	503	200	495	N/A	N/A	N/A	373

Bestobell LNG has a continuing policy of product improvement and as such the above details are subject to change at any time and without notice. Please contact Bestobell LNG for current information.

Bestobell LNG, President Park, President Way, Sheffield, S4 7UR
Tel: + 44 (0) 114 224 0000 Fax: + 44 (0) 114 2784974
E-mail: info@bestobell-lng.com Website: www.bestobell-lng.com

Rev No: 2